

Anabec Systems



*Restrictions Apply

www.Anabec.com

Toll Free: 800.369.8463

X90

X90 is a second step in the Anabec System of Products. Application of X90 results in an extremely durable moisture barrier. X90 is applied after cleaning the surface with Advanced Cleaning Solution. This product is appropriate for use on previously cleaned and/or disinfected, unfinished building material surfaces. X90 can serve as a primer for latex paints.

General Characteristics:

- Ready to Use
- Surface Penetrant

Color:

- Solid White

Coverage:

- 250-400 sq ft / gallon

Choose the **Anabec System** Better Chemistry. Superior Results.

x90

Product Info

Classification
Key Ingredient(s)

Moisture Barrier
Acrylic
Silver

Packaging / Storage

Packaged	5 gal bucket
Shelf Life	18 months
Storage Conditions	Do not Freeze Store out of reach of children

Properties

Finish after applied	Solid-White
Odor	None
pH	6.5-8.5
Viscosity	2,000-3,000 cps
Density	10.2 lbs/gal
Flash Point	>100 C
Est VOC	0.43 lbs /gal
Solubility in Water	Soluble

Application

Dilution	Ready to Use
Coverage	250-400 sq ft /gal
Air Less Sprayer	Yes
Brush	Yes
Roller	Yes
Reoccupy Space	30 mins
Dry to touch	2 hours
Dry through	18-24 hours
Clean-up	Water / Soap

Anabec Systems

www.Anabec.com

716.759.1674